

RPS-5000 Regenerative Power System

AC Source · AC Load · Grid Simulator



RPS-5000 regenerative power system delivers 30 kVA – 225 kVA of high-performance power, integrating an AC/DC source, load, and grid simulator in a single platform. With advanced waveform harmonic analysis and simulation, it ensures precise, efficient, and reliable power testing. Designed for AI server power new energy, electric vehicles (EVs), and power electronics, it not only meets IEC 61000 compliance requirements but also enhances testing flexibility and energy utilization with its bidirectional regenerative design.

KEY FEATURES

- Power range: 30 kVA – 225 kVA.
- AC source, load, and grid simulator in a single unit.
- 35% power boost with constant power capability.
- Boosts efficiency to 91% from 80%.
- 50th order harmonic analysis for advanced testing.
- Analog and digital control for PHIL testing.
- Flexible output: single, three, or split-phase.
- Auto-parallelism for capacity expansion.
- Trigger in & out enables seamless synchronization.
- LIST, PULSE, STEP, TRANSIENT, and Arbitrary Waveform.
- Multiple communication interfaces, including RS232, USB, Ethernet, and optional GPIB.
- PowerVue remote management software for intuitive operation.
- Modular design with built-in DSP enables fast maintenance and calibration.
- Function Test: IEC 61000-3-2/-3-3/-3-11/-3-12/-4-11/-4-13/-4-14/-4-28/-4-34

PowerVUE:

The remote control software supports PC-based operation, configuration, waveform monitoring, and IEC 61000 compliance testing (e.g., 4-11, 4-13, 4-14, 4-17, 4-28, 4-29).



About INFINIPOWER:

With 20+ years of R&D expertise in power testing, INFINIPOWER delivers industry-leading solutions with trusted performance, precision, and stability. Backed by world-class manufacturing from Delta Electronics and TÜV certification, INFINIPOWER empowers customers—powering trust, driving innovation in the new energy era.

Technical Specifications

Item			RPS-5030	RPS-5045
AC INPUT	Phase	3Ø3W		
	Voltage	200 - 220 V _{L-L} ± 10% / 380 - 400 V _{L-L} ± 10% / 440 - 480 V _{L-L} ± 10%		
	Frequency	47 - 63Hz		
	Max. Current / phase	66A @ 380 V _{L-L} ± 10%		99A @ 380 V _{L-L} ± 10%
	Power Factor*	0.98(Typical)		
AC OUTPUT	Phase Modes	3Ø, 1Ø or Split phase selectable		
	Max. Power	30kVA/20kVA(Split phase)		45kVA/30kVA(Split phase)
	Phase/Channel	10kVA		15kVA
AC VOLTAGE	Range	0 - 400V _{L-N} , 0 - 692V _{L-L} , 0-800V _{L-L} (Split phase)		
	Resolution / Accuracy	0.1V / ± (0.1% of setting + 0.2% F.S.)		
	Total Harmonic Distortion (THD)*	<0.4% @ 50/60Hz, <0.9% @ 30-150Hz		
	Line & Load Regulation	± 0.1% Line, ± 0.2% Load		
MAX. AC CURRENT	RMS*	200A(1Ø)/66.7A(3Ø/Split)		300A(1Ø)/100A(3Ø/Split)
	Peak	550A(1Ø)/183A(3Ø/Split)		825A(1Ø)/275A(3Ø/Split)
	Crest Factor	2.75		2.75
FREQUENCY	Range	30Hz - 150Hz		
	Resolution / Accuracy*	0.01Hz / ± 0.01% F.S.		
DC OUTPUT	Max. Power	30kW/20kW(Split phase)		45kW/30kW(Split phase)
	Per Phase/Channel	10kW		15kW
DC VOLTAGE	Range	±565VDC, ±1130VDC(Split phase)		
	Resolution / Accuracy	0.1V / ± (0.1% of setting + 0.2% F.S.)		
DC CURRENT	MAX.	200A(1Ø)/66.7A(3Ø/Split)		300A(1Ø)/100A(3Ø/Split)
HARMONIC	Synthesis Function	up to 50 Harmonic orders @ 50/60Hz fundamental frequency		
MEASUREMENT	Voltage (AC)	Range	0 - 400V _{L-N} , 0 - 692V _{L-L} , 0 - 800V _{L-L} (Split)	
		Resolution	0.01V, Accuracy: ± (0.1% of reading + 0.2% F.S.) at Voltage > 5V	
	Voltage (DC)	Range	±565VDC, ±1130VDC (Split phase)	
		Resolution / Accuracy	0.01V / ± (0.1% of reading + 0.2% F.S.) at Voltage > 5V	
	Current (AC,DC)	Range	1Ø	0.10A - 200.00A
			3Ø/Split phase	0.10A - 66.70A
		Resolution/ Accuracy		0.01A / ± (0.4% of reading + 0.3% F.S.)
	Peak Current	Range	1Ø	0.0Apk - 550.0Apk
			3Ø/Split phase	0.0Apk - 183.0Apk
		Resolution		0.1A, Accuracy: ± (0.4% of reading + 0.6% F.S.)
	Power Apparent (VA)	Range	1Ø	0.0VA - 30kVA
			3Ø/Split phase	0.0VA - 10kVA/0.0VA - 20kVA
		Resolution		0.1VA at 0.0 - 9999.9VA / 1VA at Power ≥10000VA
	Power (AC,DC)	Accuracy		V×A, Calculated value
		Range	1Ø	0.0W - 30kW
			3Ø/Split phase	0.0W - 10kW/0.0W - 20kW
		Resolution		0.1W at 0.0 - 9999.9W, 1W at Power ≥10000W
		Accuracy		± (0.4% of reading + 0.4% F.S.)
GENERAL	Interface	USB, RS232, Ethernet, External I/O(DB25), Option: GPIB, CAN Bus		
	Display	Full Color, Touch LCD Display, 7" Diagonal size, 800 x 400 Pixels resolution		
	Protection	OCP, OVP, OPP, OTP, SHORT, FAN		
	V Sense	Yes		
	Efficiency*	90% (Typical)		
	Dimension(H x W x D)(with casters)	1000 x 704 x 910 mm / 39.37 x 27.72 x 35.83 inch		
	Weight	510kg / 1124.3 lbs		
REGULATORY COMPLIANCE	Safety	Low Voltage Directive 2014/30/EU, EN 61010-1:2017		
	EMC	CE marked for EMC Directive 2014/30/EU per EN 61326-1:2013 Class A		
	CE Mark LVD Categories	Installation Overvoltage Category: II; Pollution Degree: 2; indoor use only.		

*For further details, please consult the datasheet.